

Mobil SHC Grease 100 EAL Series

Grease

Product Description

Mobil SHC Grease 101 EAL and 102 EAL are supreme performance greases designed specifically for applications which are environmentally sensitive. These leading products are biodegradable and virtually non-toxic greases formulated from a biodegradable synthetic ester base oil and a lithium soap thickener. The wax-free nature of the synthetic base fluid, together with its low traction coefficient, provide excellent low temperature pumpability and very low starting and running torque - a significant benefit considering many environmentally sensitive applications are located outdoors.

The Mobil SHC Grease 100 EAL Series is formulated for multipurpose outdoor applications where grease leakage or run out could contaminate soil, groundwater, surface water systems, or indoor plant water systems. They are recommended for plain and rolling element bearings and couplings that operate at temperatures from -30°C to 120°C with appropriate adjustments to re-lubrication interval. Mobil SHC Grease 101 EAL and 102 EAL are NLGI grade 1 and 2 respectively; both have ISO VG 100 base oils.

Extensive field evaluation and commercial experience with these products around the world has confirmed good performance in a variety of applications ranging from marble quarry chain saws to hydro-turbines. Even though they are designed for environmental benefits, Mobil SHC Grease 101 EAL and 102 EAL stand up to very demanding performance standards and help extend equipment life and keep equipment running reliably and efficiently.

Features and Benefits

The Mobil EAL brand of environmentally sensitive products has gained an exceptional reputation with OEMs and customers around the world. These products provide an exceptional balance between meaningful environmental benefits over conventional products while providing excellent performance as lubricants. Mobil SHC Grease 100 EAL Series fit this profile well with excellent biodegradability and toxicity scores, and with very good performance features especially in terms of corrosion and wear protection.

Mobil SHC Grease 100 EAL Series greases are compatible with the previous generation Mobilgrease EAL 100 Series.

Mobil SHC Grease 101 EAL and 102 EAL offer the following benefits:

Features	Advantages and Potential Benefits
Virtually non-toxic in the OECD 203 Method Aquatic Toxicity Test	Minimal effects of spills on environment
Formulated from biodegradable synthetic ester base oil	Biodegradation of material in sensitive areas with minimal non-biodegradable residue, avoidance of costly clean-up in some jurisdictions.
Good adhesion and water resistance	Resists water washout, avoiding need for frequent re-greasing



Features	Advantages and Potential Benefits
Excellent rust and corrosion protection	Excellent bearing protection in wet conditions, with long bearing life

Applications

Mobil SHC Grease 101 EAL and 102 EAL are two members of a family of Mobil Environmental Awareness Lubricants (EAL) specifically designed for applications where contamination of the environment is a risk. Mobil SHC Grease 101 EAL (NLGI Grade 1) and 102 EAL (NLGI Grade 2) are multipurpose greases formulated with an ISO VG 100 base fluid. They are designed for the lubrication of equipment in environmentally sensitive areas, including:

- Marine equipment
- Water treatment plants
- Dams, locks and water ways
- Construction equipment
- Farm machinery

Specifications and Approvals

Mobil SHC Grease 100 EAL meets the following industry specifications:	101	102
DIN 51825: (2004-06)	KPE1K-40	KPE2K-40

Typical Properties

Mobil SHC 100 Grease EAL Series	101	102
NLGI Grade	1	2
Thickener Type	Lithium	Lithium
Color, Visual	Tan	Tan
ISO Viscosity Grade of Oil	100	100
Dropping Point, ASTM D 2265, °C	180	180
Worked Penetration, ASTM D 217, mm/10 @25°C	325	280
Water Washout @ 79° C, ASTM D 1264, wt%	8.0	6.5
EMCOR Bearing Corrosion in Distilled Water, ASTM D 6138, Rating	0,0	0,0
Copper Corrosion, ASTM D 4048, Rating	1a	1a
Four Ball Weld, ASTM D 2596, kgf	200	200
Four Ball Load Wear Index, ASTM D 2596, kgf	35	34
US Steel Mobility @-18°C, g/min	-	50
Low Temperature Torque @-30°C, Start/Run, ASTM D 1478, gcm	-	800/170
Biodegradability of ester base oil, OECD 301B, wt%	74	74
Aquatic Toxicity, OECD 203, LL50 ppm	>10000	>10000



Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.